

ECORASTER® Bloxx – with integrated drainage joints

For quick and durable permeable pavement



Technical specifications

| | |
|-----------------------|--|
| Dimensions | 13 in x 13 in x 2 in |
| Weight per sq ft. | 17.4 lbs |
| Weight per unit | 20.8 lbs |
| Carrying load | Exceeds H90 and HL92 (fill/base dependent) |
| Dimensional stability | Temperature range -58°F to +194°F |
| Concrete dimensions | 5.6 in x 5.6 in x 1.75 in |
| Pressure resistance | Up to 20 t axle load in acc. with DIN 1072 |
| Material | 100% recycled LDPE and concrete |
| Available colors | Natural, black, red, grey |

Advantages

- ✓ High performance permeable paving
- ✓ Weather and salt resistant
- ✓ High load
- ✓ Very high infiltration rate
- ✓ Resistant to UV and aggressive solvents
- ✓ Seamless fit with other Ecoraster systems
- ✓ Proven safety locking system
- ✓ Made from 100% recycled LDPE
- ✓ German design
- ✓ Environmentally neutral
- ✓ Versatile applications
- ✓ Minimal maintenance

Most suitable for

Stormwater Management

Parking lots and driveways with snow conditions
Emergency and fire access lanes
Outdoor warehousing and logistic areas
Soft shoulder reinforcement
Streetcar track fill reinforcement
Roads
Oil and mining applications
Pools and decks
Accessible paths and sidewalks